



## POLYSLICK® MARINE



Ultra High Molecular Weight Polyethylene Fendering



Fender Pads



Flexi Fend®

U.S. Patent Nos. 6,832,570 /  
6,948,440 / 7,624,694 / 8,029,209



Pileguard

### APPLICATIONS

Dock Facings

Bridge Fenders

Boat Rails and Gunnels

Canal Lock Door Panels

Lock and Dam Guidewall

Dry Dock Walls and Side Rails

Pile Facings

Gate Fenders

Floating Docks

Pipeline Fenders

Wharf, Pier and Lock Fenders

Offshore Pump Station Fenders

Rub Rails

Sliding Pads

Pier Protection

Guide Rollers

Canal Lock Walls

Keel and Bilge Block Facings





**POLYSLICK®**  
**MARINE**



**UHMW-PE DOCK FENDERS AND FENDER PADS**

FEATURES

Impact resistant  
Abrasion resistant  
UV protected  
Will not corrode, rot or splinter

Resists marine borers and barnacle growth  
Non-sparking  
Can be drilled, chamfered and fabricated to meet customer specifications

COLORS

Black                      Yellow  
Custom Colors

SIZES

Thickness                      inch / mm  
0.125 to 10 / 3 to 250

**UHMW-PE FLEXI FEND®**

FEATURES

Non-marking  
Non-grabbing  
Absorbs energy  
Impervious to salt water and oil  
Leaf shape allows it to flex with impact and return to shape with no permanent damage

High visibility  
Easy installation  
Eliminates paint or tape  
Will not corrode, rot or splinter  
US patent nos. 6,832,570 / 6,948,440 / 7,624,694 / 8,029,209

COLORS

Black                      Gray  
Custom Colors

SIZES

	<u>inch / mm</u>	<u>inch / mm</u>
T x H x W	0.25 x 4 x 2.13 / 6 x 100 x 53	0.5 x 10 x 4.2 / 12 x 250 x 105
	0.375 x 4 x 2.13 / 9.5 x 100 x 53	0.625 x 10 x 4.2 / 15 x 250 x 105
	0.375 x 10 x 4.2 / 9.5 x 250 x 105	1 x 10 x 4.2 / 25 x 250 x 105



**UHMW-PE PILEGUARDS**

FEATURES

Impact resistant  
Abrasion resistant  
UV protected  
Will not corrode, rot or splinter

Resists marine borers and barnacle growth  
Non-sparking  
Can be drilled, chamfered and fabricated to meet customer specifications

COLORS

Black                      Yellow  
Custom Colors

SIZES

Thickness                      inch / mm  
1.25 / 32  
Width x Length                      12 x Up to 30 feet / 300 x Up to 9 meters

**UHMW-PE CUSTOM FENDERS**

Fenders can be fabricated, heat or cold formed to customer specifications.  
Custom colors and formulations available.

Distributed by:



Call: 1 (866) 437-7427

Email: info@polymershapes.com

www.polymershapes.com



Headquarters:

PO Box 32; 10526 AL Hwy 40

Henagar, AL 35978 USA

Ph: (256) 657-5197

Fax: (256) 657-5189

Toll Free: 1-877-POLYMER (765-9637)

Mechanical Division: Pisgah, AL

Ultrapoly Division: Tacoma, WA

Midwest Distribution: Bolingbrook, IL

West Coast Distribution: Salt Lake City, UT

Avalanche Liner Division: Oxford, WI