

DSS 13 oz. Pro Blockout is a two-sided, blockout banner material with a smooth surface. The material offers a broad color gamut with low ink consumption and is ideal for application where complete opacity is required. The material is compatible with solvent, eco-solvent, UV and screen printing. Available in widths from 38" - 126".

Material Details

| CHARACTERISTICS | TEST METHOD | METRIC | ENGLISH |
|------------------|-------------------|----------------------|-----------------------|
| Total Weight | DIN EN ISO 2286-2 | 375 g/m ² | 13 oz/yd ² |
| Yarn dtex | DIN EN ISO 2060 | 250 / 250 | 250 x 250 denier |
| Support Cloth | DIN 60001 | Polyester | Polyester |
| Type of Coating | N/A | PVC | PVC |
| Tensile Strength | DIN 53352 BS3424 | 1300 x 1030 N/5cm | 148.46 x 117.63 lb/in |
| Tear Strength | DIN53356 BS3424 | 115 x 105 N | 25.85 x 23.60 lb |

Applications

| | POP | Banner | Banner Stands | Block-out | Tradeshow Graphics | Display Systems | Indoor Banners |
|--------------|-----|--------|---------------|-----------|--------------------|-----------------|----------------|
| Applications | ■ | ■ | ■ | ■ | ■ | ■ | ■ |

Ink Printability

| Solvent | Eco Solvent | UV | Screen Printing | Latex | Dye Direct |
|---------|-------------|----|-----------------|-------|------------|
| ■ | ■ | ■ | ■ | | |

Available Sizes

| Metric (m) | English (inches) |
|-------------------------|---------------------|
| 0.965, 1.37, 1.60, 3.20 | 38", 54", 63", 126" |

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)